

PRODUCT

Interlocking ESD Floor Tiles - X Joint

TECHNICAL DATASHEET



ESD Interlocking Floor Tiles are a tough, flexible & modern flooring solution. Can be used as your primary ground & are guaranteed to give ESD performance for the life of the tile.

These electrostatic dissipative, interlocking floor tiles are ideal for use in electronics & telecommunications factories, computer server rooms, production plants; such as pharmaceutical, paint, petrochemical & certain food production facilities with risk of dust explosion (sugar, floor dust etc).

FEATURES

- Simple Installation
- Smart Modern Appearance
- Chemically Resistant
- Fire Retardant
- Environmentally Friendly

PROPERTIES

PROPERTIES	RESULT
Dimensions	497mm x 497mm
Thickness	6.8mm +/- 0.3mm
Weight	8.40kgs/m ²
Guarantee	Lifetime Manufacturer's Guarantee
Anticipated Service Life	25 Years +
Material	PVC
Joint	X Joint

To request a quotation or for more information, please call **+44 (0)1473 836200**
email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2024 Antistat.

TECHNICAL SPECIFICATIONS

PROPERTIES	TEST STANDARDS	RESULT
Slip Resistance	EN 14041:2004 DIN 51130:2004	Pass R10
Fire Performance	BS 476: Part 7 DIN 13501: 2004	Class 1 Spread of Flame Bfl-S1 Does not support combustion
Stain Resistance	EN 423	Good
Abrasion Wear Resistance	EN 13845 EN 649	Lifetime Manufacturer's Guarantee
Mechanical Resistance	DIN 53516	17N/mm ²
Resistance to Hot Objects/Solder		Good
Thickness of Wear Layer	EN 429	6 to 10mm
Hardness	ISO 868	89-92 Shore A
Impact Resistance	EN 13329-549	549kg/cm ²
Noise Reduction	EN 140-8	>46db
Determination of Length, Squareness & Straightness:	BS EN 428:1993	<0.13% / 0.5mm max.
Chemical Resistance	EN 13529	Good resistance to most commonly used chemicals. Common acid oils & gas oil - No deterioration / Not Resistant to prolonged contact
Colour Fastness	EN 50105-BO21	5

To request a quotation or for more information, please call **+44 (0)1473 836200**
 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2024 Antistat.

PERFORMANCE & TEST RESULTS

The X Joint ESD floor tile has been independently tested against EN 14041:2018:

- Resistance ($> 3.4 \times 10^4 \Omega$ and \leq to $5.0 \times 10^6 \Omega$)
- Prevents static generation (< 100 volts)

The test results guarantee that X Joint ESD floor tile complies with British Standard BS EN 61340-5-1:2016 and IEC 61340-5-1:2016

ADDITIONAL PRODUCTS


Our ESD Grounding Kit is required for fitting floor tiles. The kit includes:

1. Earth Bonding Plug
2. Conductive Grounding Tape
3. Earth Cord with 1M Ω Resistor
4. ESD Tile with Grounding Stud



(1 kit required per 50m² of ESD flooring)

We also supply Corner and Ramp tiles which allow for easy fitting and accessibility for users.



PRODUCT CODE

PRODUCT CODE	DESCRIPTION	JOINT	COLOUR	QUANTITY	SIZE (mm)
084-0020	Interlocking ESD Floor Tile	X Joint	Grey	4**	497 x 497 x 6.8*
084-0021	Interlocking ESD Floor Pictotile	X Joint	Yellow	1	497 x 497 x 6.8*
084-0022	ESD Grounding Kit (UK)	X Joint	Grey (Tile)	-	-
084-0023	Yellow Interlocking Edging Strip	X Joint	Yellow	1	497 x 90 x 6.8*
084-0024	Yellow Interlocking Corner Strip	X Joint	Yellow	1	580 x 90 x 6.8*

*+/- 0.3mm Tolerance

**Sold per sqm (4 tiles per sqm)

To request a quotation or for more information, please call **+44 (0)1473 836200**
email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2024 Antistat.