



ESD Ballpoint Pen

TECHNICAL DATASHEET



This ESD ballpoint pen is designed to be used within an EPA environment. The pen is constructed from a durable, permanently antistatic ABS (acrylonitrile butadiene styrene) material.



DETAILS	TYPICAL VALUE	
Volume Resistance	10 ⁵ – 10 ⁹ Ohms cm	
Electrostatic Decay Time	1000V to 100V in less than 1 sec	



FEATURES

- Material: ABS
- Volume Resistance: 10⁵ 10⁹ Ohms cm
- Standard colour: Black
- Permanently ESD

PRODUCT CODE	DESCRIPTION	SIZE	QUANTITY
105-0117	ESD Ballpoint Pen	Length: 141mm	Each

To request a quotation or for more information, please call +44 (0)1473 836200 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2025 Antistat.