



PRODUCT

ESD Caution Labels - logo only

TECHNICAL DATASHEET

DESCRIPTION

Yellow ESD caution labels printed with black text onto a yellow background.

TEXT CONTENT

“ATTENTION, OBSERVE PRECAUTIONS FOR HANDLING. ELECTROSTATIC SENSITIVE DEVICES”.

Note: Image shown is of 76x38mm labels, layout may vary on different sizes.

FEATURES

- Label type: Self adhesive
- Label size: Various available
- Material: Gloss paper with backing paper for all reel stock applications, suitable for automatic dispensing
- Adhesive: General purpose, strong permanent
- Colour: Yellow with black print
- Pack qty: 1,000 labels per reel
- Design: Industry standard design
- Conforms to EIA & JEDEC-14 standards

PROPERTIES

TEST ITEM	TEST METHOD	VALUE
Adhesive	RP51 General purpose permanent adhesive – acrylic, water borne. Good adhesion on variety of substrates, including non-polar surfaces, films and corrugated board. Good low temperature performance	
Tack	FTM9	18 N/25mm
Labelling Temperature – Min	-	0 °C
Service Temperature - Min	-	-20 °C
Service Temperature – Max	-	80 °C
Limitations	Not recommended for labelling highly curved surfaces.	
	Raflacoat Plus-FSC White wood free machine coated SC mid gloss face paper. Designed for quality multicolour labels requiring high contrast and fine printing detail.	

To request a quotation or for more information, please call **+44 (0)1473 836200**
email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2024 Antistat.

PROPERTIES contd.

TEST ITEM	TEST METHOD	VALUE
Backing Paper	Honey Glassine 65 Yellow transparent glassine backing paper for all reel stock applications - suitable for automatic dispensing	
Substance	ISO 536	55 g/m ²
Caliper	ISO 534	49 µm
Tensile Strength MD	ISO1924	6.0 kN/m
Tensile Strength CD	ISO1924	2.3 kN/m
Transparency	DIN 53147	49%
Roll	Raflacoat Plus-FSC White wood free machine coated SC mid gloss face paper. Designed for quality multicolour labels requiring high contrast and fine printing detail.	
Substance	ISO 536	80 g/m ²
Caliper	ISO 534	70 µm
Tensile Strength MD	ISO1924/1	5.8 kN/m
Tensile Strength CD	ISO1924/1	2.8 kN/m
Brightness	ISO 2470/1	90%
Roughness	ISO 8791	1.0 µm
Opacity	ISO 2471	88%
Gloss	Hunter 75°	64%
CIE Whiteness	ISO 11475	120%
Stiffness MD	ISO/DP 2493	0.23 mNm
Stiffness CD	ISO/DP 2493	0.13 mNm
Printability	Suitable for flexography, offset, rotogravure, screen and hot foil.	

PRODUCT CODE	DESCRIPTION	SIZE	NOTES
055-0004	Yellow ESD Caution Labels - logo only	5mm x 5mm	Per Roll

To request a quotation or for more information, please call **+44 (0)1473 836200**
 email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2024 Antistat.

To request a quotation or for more information, please call **+44 (0)1473 836200**
email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2024 Antistat.